

Ecma/TC38-TG3/2015/025 (Rev. 1 – 15 April 2015)

Annex B1 - Product environmental attributes Imaging equipment

The declaration may be published only when all rows and/or fields marked with * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

| Brand * | Ricoh | Logo | | |
|------------------------|-------------------------------------|------|--|--|
| Company name * | Ricoh Company Ltd | | | |
| Contact information * | Ricoh Europe Plc, 20 Triton Street, | | | |
| e-mail address | London, NW1 3BF, United Kingdom | | | |
| Internet site * | www.ricoh.com | | | |
| Additional information | | | | |
| | | | | |

| The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration. | | | | | | |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------|--|--|--|--|--|
| Type of product * | Production Colour Printer | | | | | |
| Commercial name * | Pro C9200 Series Exit Unit | | | | | |
| Model number * | Pro C9200 | | | | | |
| Issue date * | 12-10-2018 | | | | | |
| Intended market * | 🗌 Global 🔀 Europe 📃 Asia, Pacific & Japan 🗌 Americas 🗌 Other | | | | | |
| Additional information | | | | | | |

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B1

Annex B1 reflects Product environmental attributes relevant for Imaging products. The following items from the ECMA-370 Main body are not shown in the template:

P9.1 PTEC, ETEC and display resolution P12.1-P12.2 Ergonomic requirements.

| Model number * Issue date * | | Pro C9200 Exit Unit | Logo | | | |
|-----------------------------|------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|----------|----|------|
| | | 12-10-2018 | | | | |
| | | | | | | |
| | t environ | mental attributes - Legal requirements | | Require | | |
| Item | <u></u> | | | Yes | No | n.a. |
| P1 | | ous substances and preparations | | | | |
| P1.1* | Product | s do comply with the current European RoHS Directive. (See legal reference and N | OTE B1) | <u>X</u> | | |
| P1.2* | | s do not contain Asbestos (see legal reference). nt: Legal reference has no maximum concentration value. | | Х | | |
| P1.3* | | s do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), | | Х | | |
| | | pmofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetract | | 1- | | |
| | | ethane, methyl bromide (see legal reference). Comment: Legal reference has no n | naximum | | | |
| | | ration values. | | | | |
| P1.4* | | s do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polych /l (PCT) in preparations (see legal reference). | nlorinated | Х | | |
| P1.5* | | s do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 car | bon atoms i | in the X | | |
| | | ntaining at least 48% per mass of chlorine in the SCCP (see legal reference). | | | | |
| P1.6* | | th direct and prolonged skin contact do not release nickel in concentrations above (| 0,5 μg/cm²/\ | week X | | |
| | (see leg | al reference). | | | | |
| | | nt: Max limit in legal reference when tested according to EN1811:2011-5. | | | | |
| P1.7* | | Article 33 information about substances in articles is available at (add URL or mail icoh-europe.com | contact): | Х | | |
| P2 | Batterie | | | | | |
| P2.1* | | | | | | Х |
| 1 2.1 | | Information on proper disposal is provided in user manual. (See legal reference) | the dispose | u | | ^ |
| P2.2* | | s or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadr | nium. (See | legal | | Х |
| | referenc | | | logui | | ~ |
| P2.3* | Batterie | s and accumulators are readily removable. (See legal reference) | | | | Х |
| P3 | | nity verification & Eco design (ErP) | | | | |
| P3.1* | | duct is CE-marked to show conformance with applicable legal requirements (see le claration of Conformity can be requested at (add link or e-mail address): emo@ric e | | | | |
| P3.2* | | duct complies with the Eco design requirements for energy-related products, | on-curope. | com | Х | |
| 1 0.2 | | al reference). | | | ~ | |
| | | d information is; given in item P15 or added to this document, | | | | |
| | | available at (add URL): | | | | |
| P4 | | hable materials | | | | |
| P4.1* | | o conductor (drum, belt etc.) is used in the product, it does not contain cadmium ma erence and NOTE B1). | ax 0,01% (s | see X | | |
| P4.2* | If ink/toner is used in the product, it does not contain cadmium max 0,1% by weight (see legal reference). | | | | | |
| P4.3* | | /toner formulation/preparation is classified as hazardous or contains a substance for | | ere X | | |
| | | munity workplace exposure limits, the product/packaging is adequately labeled acc | | | | |
| | | le regulations and a Safety Data Sheet (SDS) in accordance with these requirement | nts is availa | ble | | |
| P5 | | al reference). | | | | |
| гэ Р5.1* | | g and packaging components do not contain more than 0,01% lead, mercur | v cadmium | n and X | | |
| | hexaval | ent chromium by weight of these together. | - | | | |
| P5.2* | used (se | kaging materials are marked with abbreviations and numbers indicating the nature re legal reference). | | | | |
| P5.3* | The pro | duct packaging material is free from ozone depleting substances as specified | in the Mo | ntreal X | | |
| | | (see legal reference). | | | | |
| | | nt: Legal reference has no maximum concentration values. | | | | |
| P6 | | nt information | | | | |
| P6.1* | Informat | on for recyclers/treatment facilities is available (see legal reference). | | Х | | |

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

| Model n | umber * | Pro C9200 Exit Unit | Logo | | |
|----------------|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-----------|--------|
| Issue date * | | 12-10-2018 | | | |
| | | | | | |
| | Environn | mental attributes - Market requirements (See General NOTE GN below) nental conscious design | | Requireme | nt met |
| tem | *=manda | tory to fill in. Additional information regarding each item may be found under P14. | | Yes No | n.a. |
| 77 | Design | | | | |
| | | mbly, recycling | | | |
| 7.1* | | t have to be treated separately are easily separable | | Х | |
| 7.2* | | aterials in covers/housing have no surface coating. | | <u>X</u> | |
| 27.3* | | arts > 100 g consist of one material or of easily separable materials. | | X | |
| 27.4* | | arts > 25 g have material codes according to ISO 11469 referring ISO 1043-4. | | X | |
| 7.5 | | arts are free from metal inlays or have inlays that can be removed with commonly available of the second | allable tools. | <u> </u> | |
| 7.6* | | re easily separable. (This requirement does not apply to safety/regulatory labels). | | X | |
|)7 7* | Product | | | ~ | |
| 97.7* 97.8* | Upgradin | g can be done e.g. with processor, memory, cards or drives g can be done using commonly available tools | | X X | |
| 97.8 97.9. | Opgraum Spore po | rts are available after end of production for: 7 years | | × × | |
| P7.10 | | s available after end of production for: 7 years | | × × | |
| 7.10 | | and substance requirements | | | |
| P7.11* | | cover/housing material type (e.g. plastics, metal, aluminum): | | | |
| / | | type: PC+ABS Material type: Steel Material | type: | | |
| 7.12 | | n materials of external electrical cables are PVC free. | type. | Х | |
| 7.12 77.13 | | n materials of external electrical cables are PVC free. | | × | |
| 7.13 77.14 | | plastic casing/cover parts > 25 g contain no more than $0,1\%$ weight (1000 ppm) bro | mine and 0 1 | | |
| 7.14 | weight (1 polyvinyl | 000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame i chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) ch g more than 25% post-consumer recycled content. | retardants, a | nd | |
| P7.15 | | circuit boards, PCBs (without components) are low halogen: all PCBs > 25 | | x x | |
| 1.10 | | | | JW | |
| 7 4 0 | | as defined in IEC 61249-2-21. (See NOTE B2) | | V | |
| P7.16 | | tarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: | | Х | |
| P7.17 | Marking: | emical specifications of flame retardants in printed circuit boards > 25 g (without con | nononte): | | |
| 1.11 | | | | х | |
| | , | | , CAS #: | X | |
| | | emical specifications of flame retardants in printed circuit boards (without componen | ts) > 25 g | х | |
| | | g ISO 1043-4: | | | |
| P7.18 | | ame retarded plastic parts > 25 g contain the following flame retardant substances/ | preparations | | |
| | | ations above 0,1%: cal name: | | X | |
| | | cal name: , CAS #: (See NOTE B4) cal name: , CAS #: " | | | |
| | | cal name: , CAS #: " | | | |
| | | | 4. | х | |
| 77 40 | | nemical specifications of flame retardants in plastic parts > 25 g according ISO 1043- | | N/ | |
| P7.19 | assigned | parts > 25 g, flame retardant substances/preparations above 0,1% are used which h the following Risk phrases; and Hazard statements: | | X | |
| | | | OTE B5) | X | |
| P7.20* | Postcons | umer recycled plastic material content is used in the product (See NOTE B6): | | Х | |
| | lf YES; a | t least one of the two alternatives below shall be answered; Of total plastic parts' weight > 25 g, the postconsumer recycled plastic ma (calculated as a percentage of total plastic by weight) is a)0.038%. | aterial conte | ent | |
| | or The weig | ght of recycled material is b)36.7g | | | |

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

| Model nu | umber * | Pro C9200 | 0 Exit Unit | | | Logo | | | |
|-----------------------------------------------------------------------|------------------------------------|--------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|------------------------------------|------------------------------|--------------|---------|-------|
| Issue dat | te * | 12-10-201 | 8 | | | | | | |
| Product | environ | nental attr | ributes - Market red | quirements (cont | tinued) | | Req | uiremen | t met |
| Item | | | | | | | ١ | 'es No | n.a. |
| D 7 044 | | | ance requirements (c | | | | | X | |
| P7.21* | | | terial content is used i | | , | | | Х | |
| | a) Of tota or | total plastic al plastic by | of the two alternatives parts' weight > 25 g, weight) is 0.004%. he biobased plastic ma | the biobased plastic | vered; material content (calcul | ated as a perce | entage of | | |
| P7.22* | Light so | urces are fre | ee from mercury, i.e. le becify: Number of lamp | ess than 0,1 mg/lam | p. num mercury content pe | er lamp: | mg | Х | |
| P8 | Batterie | s | | | | | | | |
| P8.1* | | | mposition: Manganese | e Dioxide Lithium | | | | | |
| P9 | | | on (See NOTE B8) | | | | | | |
| P9.1 | For the | product the f | following power levels | or energy consump | tions are reported: | | | | |
| Energy m | ode * | | Power level at 100 V AC | Power level at 115 V AC | Power level at 230 V AC | Reference/Si modes and te | | energy | / |
| | de for ENE Operational ducts | | W | W | W | | | | Х |
| Standby/off mode for ENERGY STAR Operational Mode (OM) products | | erational | W | W | W | | | | Х |
| TEC prod | | | kWh/week | kWh/week | 37.498 kWh/week | | | | |
| Operatin | /pical Energ g Mode | ју | W | W | Mono: 3237W Colour: 3610W | | | | |
| Ready M | ode | | W | W | 2160W | | | | |
| Sleep Mo | ode | | W | W | 2W | | | | |
| | | | W | W | W | | | | |
| | | | W | W | W | 1 | | | |
| | | | W | W | W | 1 | | | |
| External F | Power Sup | olv Efficienc | y Level (International I | Efficiency Marking P | Protocol) * : | | | | Х |
| Print/Sca | | - | 115 images per minute | | , - | | | | |
| | • | | 0 | , | | <u> </u> | | | |
| | | | e mode: 60 minutes | - to man data to the st | | | | V | |
| P9.2* | | | e energy save functior | is provided with the | | | | X | |
| P10 | Emissio | | Declared according to 1 | | E BO) | | | | |
| P10.1 | Mode | | Declared according to ISO 9296 (See NOTE B9) ode description Statistical upper $L_{WA,c}$ (B) Statistical upper | | Statistical upper limit A-w | eighted sound | power level, | | |
| | Idle | * | Stand-by | * | 6.4 | | | | |
| | Operatio | | Operating Mode | | 8.2 | | | | |
| | Other m | | | | | | | | |
| | Measure | ed according | | CMA-74 (only if not covered l | by FCMA-74) | | | | |

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic.

NOTE B8 A Guidance document on Energy Efficiency is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B9 A Guidance document on Acoustic Noise is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

| Model nu | mber * | Pro C9200 Exit | Unit | | | Logo | | | |
|--------------|-------------------------------------------------------------------------------------------------|----------------------------------------------|----------------------------------------------|--------------------------|-----------------|--------------|-------------|---------|-------|
| Issue date * | | 12-10-2018 | | | - | | | | |
| Product | environ | mental attribut | tes - Market requiremen | ts (continued) | | | Rea | uiremer | nt me |
| Item | | | | | | | | res No | |
| | Chemi | cal emissions fro | om printing products (See | NOTE B10) | | | | | |
| P10.2* | | | g to ECMA-328 Determination | | on Rates from F | lectronic | | Х | |
| | | | (60) , other specify: <i>RAL-</i> | | | | | ~ | |
| P10.3 | | | peration phase) is (mg/h): | 02111 | | | | | |
| 1 10.0 | | | . , , | Durat 0 7 Churana 0 10 | | | - 1 | | |
| | Electro | photographic dev | ices: Ozone Not Available I | , | | | | | |
| | | | Ozone 3.4 Dust 0 Sty | rene 0.08 Benzene < | | t Avallable | - 10000 | | |
| | Note: c | ompliance with m | aximum emission rates in ec | o labels to be declare | d in P14. | | | | |
| P11 | Consu | mable materials | for printing products | | | | | | |
| P11.1* | | | S) is available for the ink/tor | ner preparation, even i | not legally req | uired (see P | 4.3). | Х | |
| P11.2* | | | onsumer recycled fibers ca | | | | | Х | |
| | EN 122 | | - - | | | | | | |
| P11.3* | | | copying is an integrated pro | | | | | Х | |
| P11.4* | | | to end-user with default auto | o-duplex enabled. | | | | Х | |
| P13 | Packaging and documentation | | | | | | | | |
| P13.1* | Product packaging material type(s): Corrugated Paper weight (kg): 35.859 | | | | | | | | |
| | | | | eight (kg): 0.938 | | | | | |
| P13.2* | | t packaging mate | packaging is free from PVC. | eight (kg): | | | | x | |
| P13.3* | Filluuc | duct primary p | rugated fiberboard packagir | a chocify the contai | and porcontage | of minimu | | ^ | Х |
| F 13.3 | | her recovered fibe | | ig, specify the contai | neu percentage | | in post- | | ^ |
| P13.4* | Electro | nic <mark>X,</mark> Paper <mark>X</mark> , O | | , | | | | | |
| P13.5 | | | is item if paper documentation | | | | | | |
| | | | entation on paper media is c | hlorine-free: | | | | Х | |
| | If Yes, | please specify: | | | | | | | |
| | Totally | chlorine-free | | | | | | Х | |
| | | tal chlorine-free | | | | | | | |
| | | sed chlorine-free | | | | | | | |
| P14 | | ary programs: | | | | | | | |
| P14.1 | i ne pro | oduct meets the re | equirements of the following | voluntary program(s): | | | | | |
| | | SY STAR® | Criteria version: 2.0 | Date: | | category: P | roduction H | Printer | |
| | Eco-lab | | Criteria version: | Date: | | category: | | | |
| DIE | Eco-lab | | Criteria version: | Date: | Product | category: | | | |
| P15 | Additional information (See NOTE B11) Sound Pressure Level at the operator position [LpA:dB(A)] | | | | | | | | |
| | | | it the operator position [LpA:o | dB(A)] | | | | | |
| | Stand- | by: 50(dB) | : 62.8 (dB), Colour: 63.1 (dB) | | | | | | |
| | operat | ing mode. WOND. | | | | | | | |

NOTE B10 A Guidance document on Chemical Emissions is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B11 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B1

| Reference | Declaration item |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------|
| Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications. | P1.1, P4.1 |
| (EC) 1907/2006(REACH, Annex XVII | P1.2, P1.4, P1.6, P1.7, P4.2 |
| Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000, (Marketing and use of Ozone layer depleting substances) | P1.3, 5.3 |
| Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002 | P1.5 |
| "REACH" Regulation (1907/2006), annex VII | P1.10 |
| Directive 2013/56/EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator. | P2.1, P2.2, P2,3, P8.1 |
| Directive 2006/95/EC (Low Voltage Directive) | P3.1 |
| Directive 2004/108/EC (EMC Directive) | P3.1 |
| Directive 1999/5/EC (R&TTE Directive) | P3.1 |
| Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions | P3.1, P3.2 |
| Regulation (EC) 1907/2006 (REACH Regulation), Article 31, annex II) | P4.3 |
| Regulation (EC) 1272/2008 (CLP Regulation) | P4.3, P7.19 |
| Directive 2004/12/EC (Packaging Directive) | P5.1 |
| Decision 97/129/EC (Secondary packaging legislation) | P5.2 |
| Directive 2012/19/EU (WEEE directive) | P6.1 |